

CLASSIC FENJA SL 2 EP

Lithium saponified heavy duty grease semi-synthetic oil based with EP additives NLGI 2

Description

CLASSIC FENJA SL 2 EP is a special heavy-duty lithium soap grease containing semi-synthetic base oils.

Application

CLASSIC FENJA SL 2 EP is a universal lubricant for all types of antifriction and plain bearings in motor vehicles, industrial plants and construction machines. **CLASSIC FENJA SL 2 EP** is particularly recommended for lube points that are difficult to access and require infrequent lubrication.

Properties

- excellent oxidation resistance
- outstanding shear stability
- good corrosion protection properties
- resistant to high temperatures
- water resistant
- high pressure capacity
- very good adhesion

Technical data

Properties	Standard	Unit	SL 2 EP*
Operating temperature range		°C	-30 to +140
Short-time peak temperature		°C	approx. 190
Drop point	DIN ISO 2176	°C	265 to 295
Work penetration	DIN ISO 2137	1/10 mm	1 - 90
Water resistance	DIN 51 807-1		0
Base oil viscosity 40 °C	DIN 51 562	mm ² /s	approx. 800
VKA welding force	DIN 51 502		2800

* are average values and may vary in the framework of the standard.

Quality Level

KP2N-30 according to DIN 51 502