

## CLASSIC GALAR LT 75W-90 GL 5 LL

Commercial vehicle gear oil, semi synthetic SAE 75W-90 for gears with extended change intervals

### Description

**CLASSIC GALAR LT 75W-90 GL 5 LL** is a semi synthetic SAE 75W-90 high-performance transmission lubricant.

### Application

**CLASSIC GALAR LT 75W-90 GL 5 LL** is particularly suited for synchronized gear boxes and heavily loaded ones differential gears in commercial vehicles.

### Properties

- extremely high oxidation and viscosity stability at high temperatures
- effective foam resistance
- high wear protection and load capacity
- reduces drive noise
- does not affect sealing materials

### Product data

| Properties       | Unit               | 75W-90* |
|------------------|--------------------|---------|
| Density 15 °C    | g/cm <sup>3</sup>  | 0.868   |
| Viscosity 40 °C  | mm <sup>2</sup> /s | 76.3    |
| Viscosity 100 °C | mm <sup>2</sup> /s | 15.2    |
| Viscosity index  |                    | 203     |
| Pourpoint        | °C                 | -48     |

\*are average values and may vary in the framework of the standard.

### Quality level

API GL 4/ GL 5/ MT-1                      MIL PRF-2105E

### Performance

|   |                      |                          |
|---|----------------------|--------------------------|
| MB 235.8  | MB 235.11            | MAN 341 E-3 / Z-2        |
| MAN 342 M-3                                     | ARVIN MERITOR 0-76-N | DAF GL 5                 |
| IVECO   | MACK GO-J            | RENAULT B0032/ 3 Annex 3 |
| SAE J 2360                                      | SCANIA STO 1:0       | VOLVO 97312              |
| ZF TE-ML 05B/07A/08/12B/12L/12N/16F/17B/19C/21B |                      |                          |

Based on application technology experience this oil can also used in passenger car transmissions according to: VW G 501.50/501.51/G052 190/G052 911.