

CLASSIC MEDUNA PT FLEX 5W-30

Passenger car engine oil HC synthesis basic SAE 5W-30 low SAPS

Description

CLASSIC MEDUNA PT FLEX 5W-30 is a high-performance fuel-efficient engine oil based on HC synthetic base oils for modern diesel and gasoline engines of the latest technology.

With high fuel economy as well as by reducing pollutant emissions according to Euro V, **CLASSIC MEDUNA PT FLEX 5W-30** contributes to the protection of the environment.

Application

CLASSIC MEDUNA PT FLEX 5W-30 was developed for universal use in passenger car, gasoline and diesel engines and diesel particulate filters (DPF). It can be mixed with all commercially available engine oils. The operating instructions of the respective vehicle and engine manufacturers must be observed.

Properties

- excellent engine cleanliness
- especially suitable for vehicles with diesel particulate filter
- developed for the reduction of pollutant emissions according to Euro V
- long-term protection of exhaust aftertreatment systems thanks to „Low SAPS“ formulation
- universally applicable for diesel and gasoline engines
- very good wear protection even under high loads
- reduced oiling times and shorter starting times during cold starts

Product data

Properties	Unit	5W-30*
Density 15 °C	g/cm ³	0,852
Viscosity 40 °C	mm ² /s	70,9
Viscosity 100 °C	mm ² /s	12,0
Viscosity index		167
Pour point	°C	-45
Flash point (COC)	°C	220

*are average values and may vary in the framework of the standard.

Quality level

ACEA C2/C3

API SN

Performance

MB 229.31/229.51/229.52

NECO 18-1811 CLASSE SC 1

OPEL OV 040 1.547 - D30

FORD WSS-M2C917-A

BMW LONGLIFE-04

RENAULT RN 17

OPEL GM LL-A-025

HYUNDAI

FIAT 9.55535-S1/-S3

VW 505.00/505.01

OPEL GM-LL-B-025

KIA