

CLASSIC PTFE OIL SPRAY

Semi-synthetic long-term lubrication oil with PTFE additives

Description

CLASSIC PTFE OIL SPRAY is a universal lubricant made from synthetic and mineral base oils and highly effective PTFE additives. Thanks to its low coefficient of friction, polytetrafluoroethylene (PTFE) is an excellent lubricant. By combining PTFE with carefully selected base oils, we have been able to develop a top-quality product for demanding applications.

CLASSIC PTFE OIL SPRAY is a strong water repellent and rust dissolver. Due to its excellent adhesive properties, it offers effective protection against corrosion.

Application

CLASSIC PTFE OIL SPRAY can be used at precision mechanical and pressure-loaded lubrication points in a wide range of applications. It is particularly suitable for long-term lubrication and also lasts under sustained pressure.

CLASSIC PTFE OIL SPRAY protects and lubricates all moving parts and prevents noise. It is recommended for a wide range of applications for example in garages, vehicles, in the Agriculture and shipping. It is also suitable for the household and hobby area. In addition **CLASSIC PTFE OIL SPRAY** can also be used flexibly as a universal cutting oil for stainless steel machining.

CLASSIC PTFE OIL SPRAY can be used in a wide temperature range from -34 °C to +230 °C.

Properties

- Good emergency running properties thanks to solid lubricant component
- Transparent / light colour
- Water-repellent
- Highly adhesive
- Good wear protection

Product data

Properties	Unit	Value *
Density 20°C	g/cm ³	0,717
Operating temperature	°C	-34 to +230
Storage 5°C to 30°C	Month	24
Disposal (empty container)	ASN/EWC	15 01 04
Disposal (container with product)	ASN/EWC	16 05 04

* are average values and may vary in the framework of the standard