

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.10.2025

Version number 1.00

Revision: 15.04.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **CLASSIC BENZINSYSTEMREINIGER**

UFI:

Notified for: Germany
CEY0-C054-C00W-0QUU

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Other cleaning and care products for vehicles (all types)
Cleaning agent for the fuel system
Cleaning fluid for petrol system

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

CLASSIC Schmierstoff GmbH & Co. KG
Lange Straße 100-106
D-27318 HOYA
GERMANY
Phone: +49 (4251) - 8120
products@classic-oil.de

Further information obtainable from: product management

1.4 Emergency telephone number: 24-hour emergency contact number : +1 872 5888271 (CSG)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.
Skin Irrit. 2 H315 Causes skin irritation.
STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.10.2025

Version number 1.00

Revision: 15.04.2025

Trade name: **CLASSIC BENZINSYSTEMREINIGER**

(Contd. of page 1)

Hazard pictograms



GHS02 GHS05 GHS07 GHS08

Signal word Danger

Hazard-determining components of labelling:

Xylene

Alcohols, C12-13-branched and linear, ethoxylated
propan-2-ol

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics

Hazard statements

H225 Highly flammable liquid and vapour.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of this material and its container to hazardous or special waste collection point.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Determination of endocrine-disrupting properties No ingredient is listed.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 1330-20-7 EINECS: 215-535-7	Xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	20-<40%
-------------------------------------	---	---------

(Contd. on page 3)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.10.2025

Version number 1.00

Revision: 15.04.2025

Trade name: CLASSIC BENZINSYSTEMREINIGER

(Contd. of page 2)

CAS: 67-63-0 EINECS: 200-661-7	propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	10-<20%
CAS: 67-64-1 EINECS: 200-662-2	acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	10-<20%
CAS: 100-41-4 EINECS: 202-849-4	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332	1-<10%
CAS: 64742-48-9 EC number: 919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336, EUH066	1-<10%
CAS: 64742-48-9 EC number: 920-134-1 Reg.nr.: 01-2119480153-44	Naphtha (petroleum), hydrotreated heavy Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336, EUH066	1-<10%
CAS: 160901-19-9 EC number: 931-954-4	Alcohols, C12-13-branched and linear, ethoxylated Eye Dam. 1, H318; Acute Tox. 4, H302; Aquatic Chronic 3, H412	1-<10%
CAS: 224622-34-8 Reg.nr.: POLYMER	Polyetheramine Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319	1-<10%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Provide fresh air. In case of breathing difficulties or respiratory arrest, start artificial respiration. Medical treatment necessary.

After skin contact:

After contact with skin, wash immediately with soap and water.

Take off immediately all contaminated clothing.

Seek medical treatment.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: In case of vomiting, note the risk of aspiration.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

 Carbon dioxide (CO₂), foam, extinguishing powder, alcohol-resistant foam, sand.

For safety reasons unsuitable extinguishing agents: Water

5.2 Special hazards arising from the substance or mixture

Highly flammable. Vapours may form explosive mixtures with air.

5.3 Advice for firefighters

Protective equipment:

Wear self-contained breathing apparatus and chemical protection suit. Full protective suit.

(Contd. on page 4)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.10.2025

Version number 1.00

Revision: 15.04.2025

Trade name: CLASSIC BENZINSYSTEMREINIGER

(Contd. of page 3)

Mouth respiratory protective device.

Additional information

Use water spray jet to protect persons and to cool containers in the danger zone.

Knock down gases/vapours/mist with water spray jet. Collect contaminated extinguishing water separately.

Do not allow to enter drains or waterways.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Ensure adequate ventilation. Do not breathe gas/fume/vapour/aerosol.

Avoid contact with skin, eyes and clothing. Use personal protective equipment.

6.2 Environmental precautions:

Do not allow uncontrolled release of product into the environment. Explosion hazard.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomaceous earth, acid binder, universal binder).

Dispose contaminated material as waste according to section 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

For open handling, use equipment with local exhaust ventilation. Do not inhale gas/fume/vapour/aerosol.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Fumes can combine with air to form an explosive mixture.

Keep respiratory protective device available.

Handling:

Remove soiled, soaked clothing immediately. Draw up and follow a skin protection plan! Wash hands and face thoroughly before breaks and at the end of work, shower if necessary.

Do not eat, drink, smoke or snuff at the workplace.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Keep container tightly closed. Store under lock and key. Store in a place that is only accessible to authorised persons.

Ensure adequate ventilation and localised extraction at critical points.

Keep container in a cool, well-ventilated place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Do not smoke.

Information about storage in one common storage facility:

Do not store together with: Oxidising agents. Pyrophoric or self-heating hazardous substances. Foodstuffs and animal feed.

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Storage class: 3 (TRGS 510)

7.3 Specific end use(s) Cleaning fluid for petrol system

EU

(Contd. on page 5)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.10.2025

Version number 1.00

Revision: 15.04.2025

Trade name: **CLASSIC BENZINSYSTEMREINIGER**

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 67-64-1 acetone

IOELV	Long-term value: 1210 mg/m ³ , 500 ppm
-------	---

CAS: 100-41-4 ethylbenzene

IOELV	Short-term value: 884 mg/m ³ , 200 ppm
	Long-term value: 442 mg/m ³ , 100 ppm
	Skin

Additional information: The safety data sheet of the pre-supplier served as the basis for the creation.

8.2 Exposure controls

Appropriate engineering controls

For open handling, use equipment with local exhaust ventilation. Do not inhale gas/fume/vapour/aerosol.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation.

Hand protection



Protective gloves

When handling chemical substances, only chemical protective gloves with a CE mark including a four-digit test number may be worn. The design of chemical protective gloves must be selected specifically for the workplace depending on the concentration and quantity of hazardous substances.

It is recommended to clarify the chemical resistance of the above-mentioned protective gloves for special applications with the glove manufacturer.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Tightly sealed goggles

Gauze goggles

Body protection: Flame retardant clothing. Wear antistatic shoes and work clothing.

EU

(Contd. on page 6)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.10.2025

Version number 1.00

Revision: 15.04.2025

Trade name: **CLASSIC BENZINSYSTEMREINIGER**

(Contd. of page 5)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state	Liquid
Colour:	Red
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range	56 °C
Flammability	Highly flammable.
Lower and upper explosion limit	
Lower:	0.6 Vol %
Upper:	14.3 Vol %
Flash point:	-9 °C (ISO 3679)
Decomposition temperature:	Not determined.
pH	Mixture is non-soluble (in water).
Viscosity:	
Kinematic viscosity at 40 °C	0.73 mm ² /s (DIN EN ISO 3104)
Dynamic:	Not determined.
Solubility water:	No testing required as the substance is known to be insoluble in water.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 50 °C:	440 hPa (DIN EN ISO 13016-1)
Density and/or relative density	
Density at 20 °C:	0.82 g/cm ³ (DIN 12185)
Relative density	Not determined.
Vapour density	Not determined.
Particle characteristics	Does not apply to liquids.

9.2 Other information

Appearance:	
Form:	Fluid
Important information on protection of health and environment, and on safety.	
Ignition temperature:	Not determined.
Explosive properties:	Product does not present an explosion hazard.
Change in condition	
Drip point:	
Oxidising properties	The product is not: oxidising.
Evaporation rate	Not determined.

Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void

(Contd. on page 7)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.10.2025

Version number 1.00

Revision: 15.04.2025

Trade name: **CLASSIC BENZINSYSTEMREINIGER**

(Contd. of page 6)

Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void
Additional information	Continued combustibility: Self-sustaining combustion

SECTION 10: Stability and reactivity

10.1 Reactivity Highly flammable.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

The product is stable when stored at normal ambient temperatures.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid

Keep away from heat sources (e.g. hot surfaces), sparks and open flames. Vapours may form explosive mixtures with air.

10.5 Incompatible materials: Oxidising agent, strong; Acid, concentrated; Alkalis (lyes), concentrated

10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Harmful if inhaled.

LD/LC50 values relevant for classification:

CAS: 67-63-0 propan-2-ol

Oral	LD50 oral	5,840 mg/kg (Rat) (OECD Guideline 423)
Dermal	LD50 dermal	12,857 mg/kg (rabbit) (OECD Guideline 402)
Inhalative	LC50/4h	>10,000 mg/l (Rat) (OECD 403)

CAS: 67-64-1 acetone

Oral	LD50 oral	5,800 mg/kg (Rat)
Dermal	LD50 dermal	20,000 mg/kg (rabbit)
Inhalative	LC50/4h	76 mg/l (Rat)

CAS: 64742-48-9 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics

Oral	LD50 oral	>5,000 mg/kg (Rat)
Dermal	LD50 dermal	>5,000 mg/kg (rabbit)
Inhalative	LC50/4h	>5 mg/l (Rat)

CAS: 64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral	LD50 oral	>5,000 mg/kg (Rat) (OECD Guideline 401)
Dermal	LD50 dermal	>5,000 mg/kg (Rat) (OECD 403)
Inhalative	LC50/4h	>5 mg/l (Rat)

CAS: 160901-19-9 Alcohols, C12-13-branched and linear, ethoxylated

Oral	LD50 oral	>300–2,000 mg/kg (Rat)
Dermal	LD50 dermal	>2,000 mg/kg (rabbit)

Polyetheramine

Oral	LD50 oral	>5,000 mg/kg (Rat)
Dermal	LD50 dermal	>2,000 mg/kg (rabbit)

(Contd. on page 8)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.10.2025

Version number 1.00

Revision: 15.04.2025

Trade name: **CLASSIC BENZINSYSTEMREINIGER**

(Contd. of page 7)

Primary irritant effect:

Skin corrosion/irritation

Causes skin irritation.

Repeated contact can lead to chapped or cracked skin.

Serious eye damage/irritation Causes serious eye damage.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure May cause respiratory irritation. May cause drowsiness or dizziness.

STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

Additional toxicological information:

CAS: 1330-20-7 Xylene

Dermal	ATE	1,100 mg/kg
Inhalative	ATE Dust/Mist	1.5 mg/L
	ATE Vapour	11 mg/L

CAS: 100-41-4 ethylbenzene

Inhalative	ATE Dust/Mist	1.5 mg/L
	ATE Vapour	11 mg/L

CLASSIC BENZINSYSTEMREINIGER

Oral	ATE	6,184 mg/kg (Calculated)
Dermal	ATE	4,197 mg/kg (Calculated)
Inhalative	ATE Dust/Mist	4.469 mg/L (Calculated)
	ATE Vapour	32.77 mg/L (Calculated)

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

Other information

The mixture is classified as hazardous according to Regulation (EC) No 1272/2008 [CLP]. Special hazards arising from the substance or mixture!

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

Harmful to aquatic life with long lasting effects.

CAS: 67-63-0 propan-2-ol

ErC50	>100 mg/l /(72h) (Scenedesmus subspicatus)
EC50	>100 mg/L /(48h) (Daphnia magna)
LC50	>100 mg/L /(96h) (Leuciscus idus)

CAS: 67-64-1 acetone

EC50	6,100 mg/L /(48h) (Daphnia magna)
LC50	5,540 mg/L /(96h) (Oncorhynchus mykiss)

CAS: 64742-48-9 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics

ErC50	>1,000 mg/l (Pseudokirchnerella subcapitata)
EC50	>1,000 mg/L /(48h) (Daphnia magna)
LC50	>1,000 mg/L /(96h) (Oncorhynchus mykiss)

CAS: 64742-48-9 Naphtha (petroleum), hydrotreated heavy

ErC50	1,000 mg/l /(72h) (Pseudokirchnerella subcapitata) (OECD 201)
-------	---

(Contd. on page 9)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.10.2025

Version number 1.00

Revision: 15.04.2025

Trade name: CLASSIC BENZINSYSTEMREINIGER

(Contd. of page 8)

EC50	>22–<46 mg/L /(48h) (Daphnia magna) (OECD 202)
LC50	3.6 mg/L /(96h) (Oncorhynchus mykiss) (OECD 203)
CAS: 160901-19-9 Alcohols, C12-13-branched and linear, ethoxylated	
EC50	>1–10 mg/L (Daphnia magna) (OECD 202)
LC50	>1–10 mg/L /(96h) (Fish) (OECD 203)

12.2 Persistence and degradability

The product has not been tested.

CAS: 67-63-0 propan-2-ol	
Persistence and degradability	95 % /(21d) Isopropanol Readily biodegradable (according to OECD criteria).
Persistence and degradability	99 % Readily biodegradable (according to OECD criteria).
CAS: 64742-48-9 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics	
Persistence and degradability	80 % /(28d) Readily biodegradable (according to OECD criteria).

12.3 Bioaccumulative potential

The product has not been tested.

CAS: 67-64-1 acetone	
Partition coefficient n-octanol/water	-0.24 (Log Pow)

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Remark: Harmful to fish

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Dispose of waste according to applicable legislation.

Do not allow to enter drains or water courses.

Do not allow to enter the subsoil/soil.

European waste catalogue	
07 01 04*	other organic solvents, washing liquids and mother liquors

Uncleaned packaging:

Recommendation:

Handle contaminated packages in the same way as the substance itself.

(Contd. on page 10)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.10.2025

Version number 1.00

Revision: 15.04.2025

Trade name: **CLASSIC BENZINSYSTEMREINIGER**

Disposal must be made according to official regulations.

(Contd. of page 9)

SECTION 14: Transport information

14.1 UN number or ID number
ADR, IMDG, IATA

UN1993

14.2 UN proper shipping name
ADR

1993 FLAMMABLE LIQUID, N.O.S. (ACETONE, ISOPROPANOL (ISOPROPYL ALCOHOL))
1993 ENTZÜNDBARER FLÜSSIGER STOFF, N.A.G. (ACETON, ISOPROPANOL, XYLOL)

IMDG

FLAMMABLE LIQUID, N.O.S. (ACETONE, ISOPROPANOL,XYLENES)

IATA

FLAMMABLE LIQUID, N.O.S. (ACETONE, ISOPROPANOL, XYLENES)

14.3 Transport hazard class(es)

ADR



Class
Label

3 (F1) Flammable liquids.
3

IMDG, IATA



Class
Label

3 Flammable liquids.
3

14.4 Packing group
ADR, IMDG, IATA

II

14.5 Environmental hazards:

Not applicable.

14.6 Special precautions for user
Hazard identification number (Kemler code):
EMS Number:
Stowage Category

Warning: Flammable liquids.
33
F-E,S-E
B

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ)
Excepted quantities (EQ)

1L
Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

Transport category
Tunnel restriction code

2
D/E

(Contd. on page 11)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.10.2025

Version number 1.00

Revision: 15.04.2025

Trade name: **CLASSIC BENZINSYSTEMREINIGER**

(Contd. of page 10)

IMDG

Limited quantities (LQ)
Excepted quantities (EQ)

1L
Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

UN "Model Regulation":

UN 1993 FLAMMABLE LIQUID, N.O.S. (ACETONE, ISOPROPANOL (ISOPROPYL ALCOHOL)), 3, II

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02 GHS05 GHS07 GHS08

Signal word Danger

Hazard-determining components of labelling:

Xylene

Alcohols, C12-13-branched and linear, ethoxylated propan-2-ol

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, < 2% aromatics

Hazard statements

H225 Highly flammable liquid and vapour.
H332 Harmful if inhaled.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405 Store locked up.
P501 Dispose of this material and its container to hazardous or special waste collection point.

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

(Contd. on page 12)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.10.2025

Version number 1.00

Revision: 15.04.2025

Trade name: CLASSIC BENZINSYSTEMREINIGER

(Contd. of page 11)

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3,28,40,75

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

CAS: 67-64-1 | acetone

Regulation (EC) No 273/2004 on drug precursors

CAS: 67-64-1 | acetone

3

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

CAS: 67-64-1 | acetone

3

National regulations:

Information about limitation of use:

Germany:

Observe restrictions according to the Youth Employment Protection Act (JArbSchG)

Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

Other regulations, limitations and prohibitive regulations

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: All suspicious transactions and the loss and theft of significant quantities must be reported to the relevant national contact point.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 13)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.10.2025

Version number 1.00

Revision: 15.04.2025

Trade name: CLASSIC BENZINSYSTEMREINIGER

(Contd. of page 12)

Classification according to Regulation (EC) No 1272/2008

Flammable liquids	On basis of test data
Acute toxicity - inhalation Skin corrosion/irritation Serious eye damage/irritation Specific target organ toxicity (single exposure) Specific target organ toxicity (repeated exposure) Aspiration hazard Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Department issuing SDS: product management

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 2: Flammable liquids – Category 2
 Flam. Liq. 3: Flammable liquids – Category 3
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
 Asp. Tox. 1: Aspiration hazard – Category 1
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Sources The safety data sheet of the pre-supplier served as the basis for the creation.