

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.10.2025

Version number 1.00

Revision: 11.04.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **CLASSIC DIESELSYSTEMREINIGER**

UFI:

Notified for: Germany
PAY0-U0FR-200E-AD8S

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Other cleaning and care products for vehicles (all types)
Cleaning agent for the fuel system
Cleaning fluid for diesel systems

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

CLASSIC Schmierstoff GmbH & Co. KG
Lange Straße 100-106
D-27318 HOYA
GERMANY
Phone: +49 (4251) - 8120
products@classic-oil.de

Further information obtainable from: product management

1.4 Emergency telephone number: 24-hour emergency contact number : +1 872 5888271 (CSG)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.10.2025

Version number 1.00

Revision: 11.04.2025

Trade name: **CLASSIC DIESELSYSTEMREINIGER**

(Contd. of page 1)

Hazard pictograms



GHS02 GHS07 GHS08

Signal word Danger

Hazard-determining components of labelling:

Xylene
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
2-ethylhexanol
ethylbenzene

Hazard statements

H226 Flammable liquid and vapour.
H332 Harmful if inhaled.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.
P405 Store locked up.
P501 Dispose of this material and its container to hazardous or special waste collection point.
Dispose of waste according to applicable legislation.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Determination of endocrine-disrupting properties No ingredient is listed.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 64742-48-9 EC number: 918-481-9 Reg.nr.: 01-2119457273-39	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics ⚠ Asp. Tox. 1, H304, EUH066	60-<80%
CAS: 104-76-7 EINECS: 203-234-3	2-ethylhexanol ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	10-<20%
CAS: 1330-20-7 EINECS: 215-535-7	Xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	10-<20%

(Contd. on page 3)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.10.2025

Version number 1.00

Revision: 11.04.2025

Trade name: CLASSIC DIESELSYSTEMREINIGER

(Contd. of page 2)

CAS: 100-41-4 EINECS: 202-849-4	ethylbenzene ⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332	1-<10%
CAS: 64742-94-5 EC number: 919-284-0	Solvent naphtha (petroleum), heavy arom. ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H336, EUH066	1-<10%
CAS: 160901-19-9 EC number: 931-954-4	Alcohols, C12-13-branched and linear, ethoxylated ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Aquatic Chronic 3, H412	1-<10%
CAS: 91-20-3 EINECS: 202-049-5	naphthalene ⚠ Carc. 2, H351; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Acute Tox. 4, H302	0.1-<1%
CAS: 121158-58-5 EC number: 310-154-3	phenol, dodecyl-, branched ⚠ Repr. 1B, H360F; ⚠ Skin Corr. 1C, H314; Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10)	<0.1%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Provide fresh air. In case of breathing difficulties or respiratory arrest, start artificial respiration. Medical treatment necessary.

After skin contact:

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

Seek medical treatment.

After eye contact:

In case of eye contact, rinse the eyes with water for a sufficient period of time with the eyelids open, then consult an ophthalmologist immediately.

After swallowing:

In case of vomiting, be aware of the risk of aspiration. If swallowed, rinse mouth with plenty of water (only if the person is conscious) and seek medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Carbon dioxide (CO₂), foam, extinguishing powder, alcohol-resistant foam, sand.

For safety reasons unsuitable extinguishing agents: Water

5.2 Special hazards arising from the substance or mixture

Flammable. Vapours may form explosive mixtures with air.

5.3 Advice for firefighters

Protective equipment:

Wear self-contained breathing apparatus and chemical protection suit. Full protective suit.

Mouth respiratory protective device.

(Contd. on page 4)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.10.2025

Version number 1.00

Revision: 11.04.2025

Trade name: CLASSIC DIESELSYSTEMREINIGER

(Contd. of page 3)

Additional information

Use water spray jet to protect persons and to cool containers in the danger zone.
Knock down gases/vapours/mist with water spray jet. Collect contaminated extinguishing water separately.
Do not allow to enter drains or waterways.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Ensure adequate ventilation. Do not breathe gas/fume/vapour/aerosol.
Avoid contact with skin, eyes and clothing. Use personal protective equipment.

6.2 Environmental precautions:

Do not allow uncontrolled release of product into the environment. Explosion hazard.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomaceous earth, acid binder, universal binder).
Dispose contaminated material as waste according to section 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

For open handling, use equipment with local exhaust ventilation. Do not inhale gas/fume/vapour/aerosol.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Fumes can combine with air to form an explosive mixture.

Handling:

Remove soiled, soaked clothing immediately. Draw up and follow a skin protection plan! Wash hands and face thoroughly before breaks and at the end of work, shower if necessary.
Do not eat, drink, smoke or snuff at the workplace.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Keep container tightly closed. Store under lock and key. Store in a place that is only accessible to authorised persons.
Ensure adequate ventilation and localised extraction at critical points.
Keep container in a cool, well-ventilated place.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Do not smoke.

Information about storage in one common storage facility:

Do not store together with: Oxidising agents. Pyrophoric or self-heating hazardous substances. Foodstuffs and animal feed.

Further information about storage conditions: Keep container tightly sealed.

Storage class: 3 (TRGS 510)

7.3 Specific end use(s) Cleaning fluid for diesel systems

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

(OLD) Hydrocarbon mixtures, fractions (RCP group): C9-C15 aliphatics: 600 mg/m³, 2(II)

(Contd. on page 5)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.10.2025

Version number 1.00

Revision: 11.04.2025

Trade name: **CLASSIC DIESELSYSTEMREINIGER**

(Contd. of page 4)

CAS: 104-76-7 2-ethylhexanol	
IOELV	Long-term value: 5.4 mg/m ³ , 1 ppm
CAS: 100-41-4 ethylbenzene	
IOELV	Short-term value: 884 mg/m ³ , 200 ppm Long-term value: 442 mg/m ³ , 100 ppm Skin
CAS: 91-20-3 naphthalene	
IOELV	Long-term value: 30 mg/m ³ , 10 ppm

Additional information: The safety data sheet of the pre-supplier served as the basis for the creation.

8.2 Exposure controls

Appropriate engineering controls

For open handling, use equipment with local exhaust ventilation. Do not inhale gas/fume/vapour/aerosol.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.

Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation.

Hand protection



Protective gloves

When handling chemical substances, only chemical protective gloves with a CE mark including a four-digit test number may be worn. The design of chemical protective gloves must be selected specifically for the workplace depending on the concentration and quantity of hazardous substances.

It is recommended to clarify the chemical resistance of the above-mentioned protective gloves for special applications with the glove manufacturer.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Tightly sealed goggles

Gauze goggles

Body protection: Wear suitable protective clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state Liquid
Colour: Light yellow

(Contd. on page 6)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.10.2025

Version number 1.00

Revision: 11.04.2025

Trade name: **CLASSIC DIESELSYSTEMREINIGER**

(Contd. of page 5)

Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range	136–210 °C
Flammability	Not determined.
Lower and upper explosion limit	
Lower:	0.6 Vol %
Upper:	8 Vol %
Flash point:	46 °C (ISO 3679)
Decomposition temperature:	Not determined.
pH	Mixture is non-soluble (in water).
Viscosity:	
Kinematic viscosity at 40 °C	1.3 mm ² /s (DIN EN ISO 3104)
Dynamic:	Not determined.
Solubility water:	No testing required as the substance is known to be insoluble in water.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 50 °C:	0.2 hPa (DIN EN ISO 13016-1)
Density and/or relative density	
Density at 20 °C:	0.82 g/cm ³ (DIN 12185)
Relative density	Not determined.
Vapour density	Not determined.
Particle characteristics	Does not apply to liquids.

9.2 Other information

Appearance:	
Form:	Fluid
Important information on protection of health and environment, and on safety.	
Ignition temperature:	Not determined.
Explosive properties:	Product does not present an explosion hazard.
Change in condition	
Drip point:	
Oxidising properties	The product is not: oxidising.
Evaporation rate	Not determined.

Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void

(Contd. on page 7)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.10.2025

Version number 1.00

Revision: 11.04.2025

Trade name: **CLASSIC DIESELSYSTEMREINIGER**

(Contd. of page 6)

Desensitised explosives

Void

SECTION 10: Stability and reactivity

10.1 Reactivity Inflammatory.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

The product is stable when stored at normal ambient temperatures.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid

Keep away from heat sources (e.g. hot surfaces), sparks and open flames. Vapours may form explosive mixtures with air.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Harmful if inhaled.

LD/LC50 values relevant for classification:

CAS: 64742-48-9 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Oral	LD50 oral	>5,000 mg/kg (Rat) (OECD Guideline 401)
Dermal	LD50 dermal	>5,000 mg/kg (rabbit) (OECD Guideline 402)
Inhalative	LC50/4h	>5 mg/l (Rat)

CAS: 104-76-7 2-ethylhexanol

Oral	LD50 oral	2,047 mg/kg (Rat) (OECD Guideline 401)
Dermal	LD50 dermal	>3,000 mg/kg (Rat) (OECD Guideline 402)

CAS: 160901-19-9 Alcohols, C12-13-branched and linear, ethoxylated

Oral	LD50 oral	>300–2,000 mg/kg (Rat)
Dermal	LD50 dermal	>2,000 mg/kg (rabbit)

Primary irritant effect:

Skin corrosion/irritation

Causes skin irritation.

Repeated contact can lead to chapped or cracked skin.

Serious eye damage/irritation Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure May cause respiratory irritation.

STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

Additional toxicological information:

CAS: 104-76-7 2-ethylhexanol

Inhalative	ATE Dust/Mist	1.5 mg/L
	ATE Vapour	11 mg/L

CAS: 1330-20-7 Xylene

Dermal	ATE	1,100 mg/kg
Inhalative	ATE Dust/Mist	1.5 mg/L

(Contd. on page 8)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.10.2025

Version number 1.00

Revision: 11.04.2025

Trade name: **CLASSIC DIESELSYSTEMREINIGER**

(Contd. of page 7)

	ATE Vapour	11 mg/L
CAS: 100-41-4 ethylbenzene		
Inhalative	ATE Dust/Mist	1.5 mg/L
	ATE Vapour	11 mg/L
CAS: 91-20-3 naphthalene		
Oral	ATE	500 mg/kg
CLASSIC DIESELSYSTEMREINIGER		
Oral	ATE	>2,000 mg/kg (Calculated)
Dermal	ATE	>2,000 mg/kg (Calculated)
Inhalative	ATE Dust/Mist	4.412 mg/L (Calculated)
	ATE Vapour	>20 mg/L (Calculated)

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

Other information

The mixture is classified as hazardous according to Regulation (EC) No 1272/2008 [CLP]. Special hazards arising from the substance or mixture!

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

Harmful to aquatic life with long lasting effects.

CAS: 64742-48-9 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

ErC50 1,000 mg/l /(72h) (Pseudokirchnerella subcapitata)

EC50 1,000 mg/L /(48h) (Daphnia magna)

LC50 1,000 mg/L /(96h) (Oncorhynchus mykiss)

CAS: 104-76-7 2-ethylhexanol

ErC50 11.5 mg/l /(72h) (Sq)

EC50 39 mg/L /(48h) (Daphnia magna)

LC50 17.1 mg/L /(96h) (Leuciscus idus)

CAS: 160901-19-9 Alcohols, C12-13-branched and linear, ethoxylated

EC50 >1-10 mg/L (Daphnia magna) (OECD 202)

LC50 >1-10 mg/L /(96h) (Fish) (OECD 203)

12.2 Persistence and degradability

The product has not been tested.

CAS: 64742-48-9 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Persistence and degradability 80 % /(28d)

CAS: 104-76-7 2-ethylhexanol

Persistence and degradability >80 % /(14d)

CAS: 121158-58-5 phenol, dodecyl-, branched

Persistence and degradability 10 % /(56d)

Dissolved organic carbon (DOC).

Not readily biodegradable (according to OECD criteria)

12.3 Bioaccumulative potential

The product has not been tested.

CAS: 64742-48-9 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Partition coefficient n-octanol/water 4.2-7.2 (Log Pow)

(Contd. on page 9)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.10.2025

Version number 1.00

Revision: 11.04.2025

Trade name: **CLASSIC DIESELSYSTEMREINIGER**

(Contd. of page 8)

CAS: 121158-58-5 phenol, dodecyl-, branched

BCF	794.33
Partition coefficient n-octanol/water	7.14 (Log Pow)

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Remark: Harmful to fish

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Dispose of waste according to applicable legislation.

Do not allow to enter drains or water courses.

Do not allow to enter the subsoil/soil.

European waste catalogue

07 01 04*	other organic solvents, washing liquids and mother liquors
-----------	--

Uncleaned packaging:

Recommendation:

Handle contaminated packages in the same way as the substance itself.

Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number or ID number

ADR, IMDG, IATA

UN3295

14.2 UN proper shipping name

ADR

IMDG, IATA

UN3295 HYDROCARBONS, LIQUID, N.O.S.

HYDROCARBONS, LIQUID, N.O.S.

(xylene; ethylbenzene)

14.3 Transport hazard class(es)

ADR



Class

3 (F1) Flammable liquids.

(Contd. on page 10)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31


Printing date 29.10.2025

Version number 1.00

Revision: 11.04.2025

Trade name: **CLASSIC DIESELSYSTEMREINIGER**

(Contd. of page 9)

Label	3
IMDG, IATA	
	
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	ENVIRONMENTALLY HAZARDOUS: no
14.6 Special precautions for user	Warning: Brennbare Flüssigkeit
Hazard identification number (Kemler code):	30
EMS Number:	F-E,S-D
Stowage Category	A
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3295 HYDROCARBONS, LIQUID, N.O.S. 3, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02

GHS07

GHS08

Signal word Danger

Hazard-determining components of labelling:

Xylene

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

(Contd. on page 11)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.10.2025

Version number 1.00

Revision: 11.04.2025

Trade name: CLASSIC DIESELSYSTEMREINIGER

(Contd. of page 10)

2-ethylhexanol

ethylbenzene

Hazard statements

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of this material and its container to hazardous or special waste collection point.

Dispose of waste according to applicable legislation.

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3,28,30,40,75

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

National regulations:

Information about limitation of use:

Germany:

Observe restrictions according to the Youth Employment Protection Act (JArbSchG)

Waterhazard class:

(according to AwSV, Germany)

Water hazard class 2 (Self-assessment): hazardous for water.

Other regulations, limitations and prohibitive regulations

Substances of very high concern (SVHC) according to REACH, Article 57

CAS: 121158-58-5 | phenol, dodecyl-, branched

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

EU

(Contd. on page 12)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.10.2025

Version number 1.00

Revision: 11.04.2025

Trade name: **CLASSIC DIESELSYSTEMREINIGER**

(Contd. of page 11)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H360F May damage fertility.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

Flammable liquids	On basis of test data
Acute toxicity - inhalation Skin corrosion/irritation Serious eye damage/irritation Specific target organ toxicity (single exposure) Specific target organ toxicity (repeated exposure) Aspiration hazard Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Department issuing SDS: product management

Abbreviations and acronyms:

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- SVHC: Substances of Very High Concern
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Corr. 1C: Skin corrosion/irritation – Category 1C
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Dam. 1: Serious eye damage/eye irritation – Category 1
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Carc. 2: Carcinogenicity – Category 2
- Repr. 1B: Reproductive toxicity – Category 1B
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

(Contd. on page 13)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.10.2025

Version number 1.00

Revision: 11.04.2025

Trade name: CLASSIC DIESELSYSTEMREINIGER

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Sources The safety data sheet of the pre-supplier served as the basis for the creation.

(Contd. of page 12)

EU