

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CLASSIC PTFE ÖL-SPRAY 230 °C (5901436)

Revision date: 21.02.2024

Product code: 5901436

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

CLASSIC PTFE ÖL-SPRAY 230 °C (5901436)

UFI: F6D3-609G-600V-587W

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Lubricants, greases, release products

Uses advised against

Do not use in cavities.

1.3. Details of the supplier of the safety data sheet

Company name: CLASSIC Schmierstoff GmbH & Co. KG
 Street: Lange Straße 100 - 106
 Place: D-27318 Hoya
 Telephone: +49 4251 812-0
 E-mail: products@classic-oil.de
 Internet: https://classic-oil.de/
 Responsible Department: Productmanagement

1.4. Emergency telephone number:

24-hour emergency contact number : +1 872 5888271 (CSG)

Further Information

Restricted to professional users. Follow the instructions for use on the label. To avoid risks to man and the environment, comply with the instructions for use.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aerosol 1; H222-H229

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:



Hazard statements

H222 Extremely flammable aerosol.
 H229 Pressurised container: May burst if heated.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Additional advice on labelling

Classification according to Regulation (EC) No 1272/2008 [CLP]

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CLASSIC PTFE ÖL-SPRAY 230 °C (5901436)

Revision date: 21.02.2024

Product code: 5901436

Page 2 of 12

2.3. Other hazards

Wear suitable protective clothing, gloves and eye/face protection. In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Chemical characterization

Mixture of substances listed below with nonhazardous additions:

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
74-98-6	propane			20 - < 25 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Press. Gas (Comp.); H220 H280			
106-97-8	Butane (<0.1% butadiene (EINECS 203-450-8))			10 - < 15 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Press. Gas (Comp.); H220 H280			
75-28-5	Isobutane (<0.1% 1,3-butadiene (EINECS 203-450-8))			1 - < 5 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Press. Gas (Comp.); H220 H280			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
74-98-6	200-827-9	propane	20 - < 25 %
	inhalation: LC50 = > 20 mg/l (dusts or mists)		
106-97-8	203-448-7	Butane (<0.1% butadiene (EINECS 203-450-8))	10 - < 15 %
	inhalation: LC50 = 50 - 658 mg/l (dusts or mists); dermal: LD50 = 5000 mg/kg; oral: LD50 = 5000 mg/kg		
75-28-5	200-857-2	Isobutane (<0.1% 1,3-butadiene (EINECS 203-450-8))	1 - < 5 %
	inhalation: LC50 = 658 mg/l (dusts or mists)		

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

First aider: Pay attention to self-protection! Remove contaminated, saturated clothing immediately. In all cases of doubt, or when symptoms persist, seek medical advice. Remove persons to safety. Keep away from unprotected people. Keep upwind.

After inhalation

Provide fresh air. Seek medical attention if problems persist.
Remove casualty to fresh air and keep warm and at rest.

After contact with skin

Remove mechanically (e.g. dab away using wadding or cellulose material) then thoroughly wash the affected skin with a mild cleansing agent and water. Remove contaminated clothing immediately and dispose off safely. If symptoms persist consult a doctor.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CLASSIC PTFE ÖL-SPRAY 230 °C (5901436)

Revision date: 21.02.2024

Product code: 5901436

Page 3 of 12

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eyelids open. Protect the injured eye. Consult an ophthalmologist.

After ingestion

No usual way of intake because of aerosol.
Following ingestion Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person or a person with cramps. If symptoms persist consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.
The following symptoms may occur: difficulties of breathing. Headache. Dizziness. Dizziness. Coughing. Nausea.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂). Dry extinguishing powder. Foam. Water spray jet.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Heating causes rise in pressure with risk of bursting. Vapours can form explosive mixtures with air. Thermal decomposition can lead to the escape of irritating gases and vapours. In case of fire and/or explosion do not breathe fumes.

In case of fire may be liberated: carbon monoxide (CO). Carbon dioxide (CO₂). Organic cracking products.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Wear chemical resistant suit.

Additional information

Contaminated fire-fighting water must be collected separately. Co-ordinate fire-fighting measures to the fire surroundings.

Dispose of fire residues and extinguishing water in accordance with official regulations.

Use water spray jet to protect personnel and to cool endangered containers. Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Provide adequate ventilation. Wear personal protection equipment.
Do not breathe gas/fumes/vapour/spray.

For non-emergency personnel

Keep away from unprotected people. Keep upwind. Remove persons to safety.

For emergency responders

Do not breathe gas/fumes/vapour/spray. Wear personal protection equipment. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains. Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CLASSIC PTFE ÖL-SPRAY 230 °C (5901436)

Revision date: 21.02.2024

Product code: 5901436

Page 4 of 12

Take up mechanically, placing in appropriate containers for disposal.

For cleaning up

Wipe up with absorbent material (eg. cloth, fleece). To avoid the risks of fires, all contaminated materials should be washed out well with warm soapy water before disposal.

Other information

Use non-sparking tools. Ventilate affected area.

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Treat the recovered material as prescribed in the section on waste disposal. Disposal: see section 13.

Safe handling: see section 7. Personal protection equipment: see section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Do not use in cavities. Keep away from sources of ignition - No smoking. Flammable vapours can accumulate in head space of closed systems. Pressurised container: May burst if heated. Avoid contact with skin and eyes.

Advice on protection against fire and explosion

Take precautionary measures against static discharges. Vapours may form explosive mixtures with air. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on naked flames or any incandescent material.

Advice on general occupational hygiene

Work in well-ventilated zones or use proper respiratory protection. Do not eat, drink, smoke or sneeze at the workplace. Wash hands before breaks and after work. Apply skin care products after work. Wear personal protection equipment. Take off contaminated clothing and wash it before reuse.

Further information on handling

Heating causes rise in pressure with risk of bursting.

After use replace the closing cap immediately.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Observe the storage regulations of the TRGS 300 for flammable aerosols.

Hints on joint storage

Note joint storage restrictions of Technical Rules TRGS 509 and TRGS 510.

Further information on storage conditions

Protect against: heat. UV-radiation/sunlight. frost. moisture.

10 - 30 °C

Do not store at temperatures over: 50 °C

The official regulations for the storage of compressed gas packages must be observed.

7.3. Specific end use(s)

Lubricants, greases, release products. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice on limit values

The lists valid during the making were used as basis.

8.2. Exposure controls

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CLASSIC PTFE ÖL-SPRAY 230 °C (5901436)

Revision date: 21.02.2024

Product code: 5901436

Page 5 of 12



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations. Have eye showers and safety shower ready. Provide earthing of containers, equipment, pumps and ventilation facilities.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses. EN 166

Hand protection

Protect skin by using skin protective cream.

Tested protective gloves are to be worn: EN ISO 374

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Breakthrough times and swelling properties of the material must be taken into consideration.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Protective clothing: Body protection must be selected depending on the activity and possible impact.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Suitable respiratory protective equipment: Self-contained respirator (breathing apparatus). Observe the wear time limits according to GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

Thermal hazards

Extremely flammable aerosol. Pressurized container: May burst if heated.

Environmental exposure controls

Leakage into the environment must be prevented. Do not allow uncontrolled leakage of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	mit weißem Powder
Odour:	like: Aerosol propellant.
Odour threshold:	not determined
Melting point/freezing point:	Not applicable, aerosol
Boiling point or initial boiling point and boiling range:	-42 °C
Flammability:	not determined
Lower explosion limits:	1 vol. %
Upper explosion limits:	10,9 vol. %
Flash point:	< 0 °C
Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
pH-Value:	Not applicable, aerosol
Viscosity / kinematic:	not determined
Water solubility:	Immiscible

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CLASSIC PTFE ÖL-SPRAY 230 °C (5901436)

Revision date: 21.02.2024

Product code: 5901436

Page 6 of 12

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

not determined

Vapour pressure:

not determined

Vapour pressure:

not determined

Density (at 20 °C):

 0,65 g/cm³

Relative vapour density:

not determined

Particle characteristics:

Contains no nanomaterial.

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Self-ignition temperature

Solid:

not determined

Gas:

not determined

Oxidizing properties

not determined

Other safety characteristics

Evaporation rate:

not determined

Viscosity / dynamic:

not determined

Further Information

Contains: Polytetrafluoroethylene (PTFE)

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non-reactive under normal use conditions.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No known hazardous reactions. In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

10.4. Conditions to avoid

 heat. UV-radiation/sunlight. frost. Ignition hazard. Keep away from sources of ignition - No smoking. Protect from moisture. In case of exceeding the storage temperature: $T > 50\text{ °C}$ = Danger of bursting container.

10.5. Incompatible materials

Oxidizing agents, strong.

10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapors.

 In case of fire may be liberated: carbon monoxide (CO). Carbon dioxide (CO₂). Organic cracking products.

Further information

 In case of exceeding the storage temperature: $>50\text{ °C}$ Danger of bursting container.

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CLASSIC PTFE ÖL-SPRAY 230 °C (5901436)

Revision date: 21.02.2024

Product code: 5901436

Page 7 of 12

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
74-98-6	propane				
	inhalation (4 h) dust/mist	LC50 > 20 mg/l	Rat (Rattus).	MSDS	
106-97-8	Butane (<0.1% butadiene (EINECS 203-450-8))				
	oral	LD50 5000 mg/kg	Rat (Rattus).	MSDS	
	dermal	LD50 5000 mg/kg	Rabbit	MSDS	
	inhalation (4 h) dust/mist	LC50 50 - 658 mg/l	Rat (Rattus).	MSDS	
75-28-5	Isobutane (<0.1% 1,3-butadiene (EINECS 203-450-8))				
	inhalation (4 h) dust/mist	LC50 658 mg/l	Rat (Rattus).	MSDS	

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

inhalation, Dermal, Eye contact

11.2. Information on other hazards
Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Further information

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

SECTION 12: Ecological information
12.1. Toxicity

Based on available data, the classification criteria are not met.

Leakage into the environment must be prevented.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CLASSIC PTFE ÖL-SPRAY 230 °C (5901436)

Revision date: 21.02.2024

Product code: 5901436

Page 8 of 12

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
74-98-6	propane					
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A The Ecosar class program has been develo
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	algae	USEPA OPPT Risk Assessment Division (200) Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200) Calculation using ECOSAR Program v1.00.
106-97-8	Butane (<0.1% butadiene (EINECS 203-450-8))					
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A The Ecosar class program has been develo
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	algae	USEPA OPPT Risk Assessment Division (200) Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200) Calculation using ECOSAR Program v1.00.
75-28-5	Isobutane (<0.1% 1,3-butadiene (EINECS 203-450-8))					
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A The Ecosar class program has been develo
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	algae	USEPA OPPT Risk Assessment Division (200) Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200) Calculation using ECOSAR Program v1.00.

12.2. Persistence and degradability

No further relevant information available.

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
74-98-6	propane	2,31
106-97-8	Butane (<0.1% butadiene (EINECS 203-450-8))	1,09 - 2,89
75-28-5	Isobutane (<0.1% 1,3-butadiene (EINECS 203-450-8))	1,09

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CLASSIC PTFE ÖL-SPRAY 230 °C (5901436)

Revision date: 21.02.2024

Product code: 5901436

Page 9 of 12

Further information

Doesn't get into the sewage water as long as the process is carried out according to regulations.
Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.
slightly hazardous to water (WGK 1)

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Consult the appropriate authorities about waste disposal. Dispose of waste according to applicable legislation. Dispose of this material and its container to hazardous or special waste collection point. Completely emptied packings can be re-cycled.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Only take completely empty aerosol cans to the recycling collection. Return cans that are not completely empty to the collection point for household chemicals. Recycle sales packaging via DSD (Duales System Deutschland).

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2
Tunnel restriction code:	D



Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CLASSIC PTFE ÖL-SPRAY 230 °C (5901436)

Revision date: 21.02.2024

Product code: 5901436

Page 10 of 12



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1



Marine pollutant: Nein
 Special Provisions: 63, 190, 277, 327, 344, 381,959
 Limited quantity: 1000 mL
 Excepted quantity: E0
 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS, flammable
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1



Special Provisions: A145 A167 A802
 Limited quantity Passenger: 30 kg G
 Passenger LQ: Y203
 Excepted quantity: E0
 IATA-packing instructions - Passenger: 203
 IATA-max. quantity - Passenger: 75 kg
 IATA-packing instructions - Cargo: 203
 IATA-max. quantity - Cargo: 150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Keep away from sources of ignition - No smoking.

14.7. Maritime transport in bulk according to IMO instruments

No data available

Other applicable information

Transport as "limited quantity" according to chapter 3.4 ADR/RID.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CLASSIC PTFE ÖL-SPRAY 230 °C (5901436)

Revision date: 21.02.2024

Product code: 5901436

Page 11 of 12

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

Directive 2004/42/EC on VOC in paints and varnishes: < 50 % (< 325 g/l)

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

Additional information

REACH Regulation (EC) No 1907/2006, as last amended by Commission Regulation (EU) 2022/586

CLP Regulation (EC) No 1272/2008, as last amended by Regulation (EU) 2021/1962

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,15.

Abbreviations and acronyms

Flam. Gas: Flammable gases

Aerosol: Aerosols

Press. Gas (Comp.): Compressed gas

 For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>

ADR: Accord européen sur le transport des marchandises dangereuses par Route (Europäisches

Übereinkommen über die internationale Beförderung gefährlicher Güter auf der Straße) IMDG: International

Maritime Code for Dangerous Goods (Internationaler Seeschiffahrtscode für gefährliche Güter) IATA:

International Air Transport Association (Internationaler Luftverkehrsverband) GHS: Global harmonisiertes

System zur Einstufung und Kennzeichnung von Chemikalien EINECS: Europäisches Verzeichnis der auf dem

Markt vorhandenen chemischen Stoffe ELINCS: European List of Notified Chemical Substances CAS:

Chemical Abstracts Service LC50: Tödliche Konzentration, 50% LD50: Tödliche Dosis, 50%

Key literature references and sources for data

Information from our suppliers as well as data from the "Database of registered substances" of the European

Chemicals Agency (ECHA) were used for the preparation of this safety data sheet. Other sources:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidance on the compilation of safety data sheets as amended (ECHA).

Guidance on labelling and packaging under Regulation (EC) No 1272/2008 (CLP) as amended (ECHA).

Safety data sheets of the ingredients.

ECHA homepage - Information on chemicals.

GESTIS substance database (Germany).

Federal Environment Agency "Rigoletto" - Information page on water-polluting substances (Germany).

EU occupational exposure limit values Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831 as amended.

National occupational exposure limit value lists of the respective countries in the respective valid version.

Regulations on the transport of dangerous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CLASSIC PTFE ÖL-SPRAY 230 °C (5901436)

Revision date: 21.02.2024

Product code: 5901436

Page 12 of 12

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. This information is intended to give you indications for the safe handling of the product mentioned in this safety data sheet during storage, processing, transport and disposal. The details are not transferable to other products. Insofar as the product is mixed with other materials, mixed or processed, or subjected to processing, the information in this safety data sheet, unless expressly stated otherwise, can not be transferred to the new material produced in this way.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Lubricants, greases, release products, Industrial spraying, Non industrial spraying	-	3, 22	24	7, 11	-	-	-	Aerosol

LCS: Life cycle stages

PC: Product categories

ERC: Environmental release categories

TF: Technical functions

SU: Sectors of use

PROC: Process categories

AC: Article categories

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)